

DC wall-mounted series parameter table (European standard)

| Item | Standard parameter value | | | |
|--|--|---|---------------------|---------------------|
| Product Number | JS-DC-BGS-01 | JS-DC-BGS-02、JS-DC-BGS-03 | JS-DC-BGS-03 | |
| power (output) | 7KW | 20KW | 30KW | 40KW |
| Input voltage | AC240V±20% | | AC400V±20% | |
| Output voltage | 200~600VDC | 200~750VDC | 200~1000VDC | |
| Output current | 0-20A | 0-50A | 0-100A | 0-130A |
| Input frequency | 50~60Hz | | | |
| Implementation standards | IEC/EN 61851-1,IEC/EN 61851-21-2,EN 301 489-1/3/17,EN 301 908-1/2/13 | | | |
| Interface | — | 4.3 inches LCD color display (Optional) | | |
| payment method | One-touch start/stop/plug and play | Plug-and-play charging, swipe card start-stop, swipe card billing, network scanning code (C radio frequency card (optional)) | | |
| Protection grade | ≥ IP66 | ≥ IP54 | | |
| Installation method | Wall-mounted / Pole-mounted (Pole optional) | | | |
| Gunline length (customisable) | 5m | | | |
| Weight (varies slightly by product line) | 17Kg | 122Kg | | |
| Dimension (varies slightly by product line) | 375*210*545mm 335*140*490mm | 560*380*200mm | 670*580*240mm | 670*580*240mm |
| OCCP | OCCP 1.6J | | | |
| Network interface | Ethernet,WIFI,4G | | | |
| Working temperature | -30~ +70°C (Output degraded above 50°C) | | | |
| Charging Standards | CE -JSDC24016A- BG2 | CE -JSDC38030A- BG2 | CE -JSDC38043A- BG3 | CE -JSDC38075A- BG3 |

